

WERTHER INTERNATIONAL INC.

DISTRIBUTED BY: AIR & VACUUM PROCESS, INC. TEL. 281-866-9700

FAX. 281-866-9717

SALES@AIRVACUUMPROCESS.COM

SILENT AIR COMPRESSOR

P 50 TC AL




ISO 13485-2008



ITEM # M03090US - 115V/50-60 HZ ITEM # M03010 -220V/50-60 HZ

- Completely silent operation
- Internally powder coated air tank
- Pressure switch allowing for automatic start/stop
- Outlet pressure regulator and shut off
- 5 Micron Outlet Moisture Filter/optional autodrain
- Tank pressure and outlet pressure gauges
- ASME safety valve
- Conveniently located top tank drain
- Long service life backed by a 24 month warranty and dedicated tech support



HP	0.5
Output Free Air	2.1 CFM
Output Free Air	60 L. Min
Max Pressure PSI	120 PSI
Max Pressure Bar	8 bar
Max Current 115V	4.8 Amps
Max Current 220V	2.4 Amps
Noise Level	40 db/A
Tank Size Gal.	0.93
Tank Size Lt.	3.5
Dimensions (ins.)	12 x 13 x 14
Weight	46 lbs
Packaged Dimensions	14 x 15 x 17
Packaged Weight	54 lbs

*Higher Pressure Available Upon Request



FROM THE ANALYSIS OF THE APPLICATION TO THE TREATMENT OF THE AIR, WERTHER INC. IS IN A UNIQUE POSITION TO SUPPLY THE MOST SUITABLE COMPRESSOR AND CORRESPONDING ACCESSORIES TAILORED TO THE CUSTOMER'S NEEDS.